

DENSO JGR™ PRIMER

Butyl Mastic Primer

Description

Denso JGR Primer is a quick drying, solvent based primer, specially designed to promote maximum adhesion of Denso JGR Mastic.

Uses

Denso JGR Primer is designed to promote adhesion of Denso JGR Mastic to concrete surfaces.

Features

- Fills surface irregularities for intimate contact of Denso JGR Mastic compound
- Stable over a wide temperature range
- Promotes high adhesion
- High penetration of porous substrates
- Fast drying
- Brush applied

Application

Brush down sealing surface to remove foreign material. Ensure surface to be coated is free from moisture. The surface temperature shall be minimum 3°C over dew point. The product temperature shall be minimum 3°C above dew point and temperature $\geq 10^{\circ}\text{C}$.

Thoroughly stir the primer in its container to ensure uniformity prior to use. Apply a thin coating by brush. For maximum performance, allow surface to tack dry before applying mastic.



Denso JGR™ Primer

PROPERTY SPECIFICATIONS

PROPERTIES	VALUE
Flash Point	<0°C
Application Temperature (product)	10°C min.
Product Size	1 L
Packaging	9/Carton

SHELF-LIFE

≥12 Months when stored between 0°C and 30°C in dry, ambient conditions, in original cartons and away from heat and direct sunlight



DENSO (AUSTRALIA) PTY LTD

77 - 95 National Boulevard

Campbellfield, VIC 3061

Tel: +61 3 9356 7600

Fax: +61 3 9356 7699

www.densoaustralia.com.au

A Member of the Winn & Coales International

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.