

DENSO MB-50 TAPE

All Purpose Polyolefin Fabric/Bitumen Pipeline Tape

Description

Denso MB-50 Tape is a tough, dimensionally stable, woven polyolefin fabric backing, laminated to a thick layer of polymer modified bitumen pressure sensitive adhesive.

Uses

For the anti-corrosion protection of buried or immersed pipes and fittings. The tapes can be applied by hand or machine to weld joints, bends, bare pipe lengths and pipe fittings.

Features

- Applied to marginally prepared surfaces (SSPC SP 2-3)
- Meets AWWA C209 Standard
- Cold applied
- Good conformability
- Good impact resistance
- Excellent adhesion to pipe and self
- Excellent resistance to cathodic disbonding
- Compatible with common pipe coatings

Application

Prepare surfaces by removing all loose scale, rust or other foreign matter by grit blasting or wire brush. Surface must be clean, dry and free of grease. Apply thin film of Denso Primer D to all surfaces to be wrapped and allow to dry. Peel back interleaving and apply adhesive side of the tape to the primed surface and press down. Apply the tape spirally with enough tension to make it conform. Remove interleaving as wrapping proceeds. Overlap each turn by at least 1" (25 mm) or 55% to achieve double thickness.

Irregular surfaces such as valves, flanges, etc. may require the use of Denso Mastic or Denso Profiling Mastic. Refer to the product sheets for these specific products for information on application and selection.



Denso MB-50 Tape

Property Specifications

PROPERTIES	VALUE
Thickness (ASTM D1000)	
Backing	0.65 mm
Adhesive	0.65 mm
Total	1.30 mm
Weight	1.2 kg/m ²
Breaking Strength (ASTM 1000)	5 N/mm
Tear Strength (ASTM 1004)	24 N
Grab Tensile Strength (Warp)	650 N
Trapezoidal Tear Strength (Warp)	400 N
Elongation	
Warp	19%
Weft	15%
Adhesion Peel Strength (ASTM D1000)	
To Primed Steel	2.7 N/mm
To Self	2.7 N/mm
Impact Strength (ASTM G-14)	5 Nm
Dielectric Strength	20 Kv
Maximum Service Temperature	70°C
Recommended Holiday Test Voltage	
Single Layer	10 Kv
Double Layer	15 Kv

Quantity Estimates

Tape Width	Tape Length	Rolls/ Case	Coverage with 1" (25 mm) Overlap	Coverage with 55% Overlap
in.	ft.	ea.	ea.	ea.
2" (50 mm)	50' (15 m)	24	90 ft ² /case (8.3 m ² /case)	100 ft ² /case (9.3 m ² /case)
4" (100 mm)	50' (15 m)	12	150 ft ² /case (13.9 m ² /case)	100 ft ² /case (9.3 m ² /case)
6" (150 mm)	50' (15 m)	8	168 ft ² /case (15.6 m ² /case)	100 ft ² /case (9.3 m ² /case)



DENSO (AUSTRALIA) PTY LTD

77 - 95 National Boulevard
Campbellfield, VIC 3061
Tel: +61 3 9356 7600
Fax: +61 3 9356 7699

www.densoaustralia.com.au

| Member of the Winn & Coales International

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.