

# **DENSO PRIMER D**

## **Bitumen Tape Primer**

### **Description**

Denso Primer D is an oxidised bitumen dissolved in an aromatic hydrocarbon solvent. It may be brush or spray applied on metal or concrete surfaces.

### **Uses**

Denso Primer D is designed to promote adhesion of bitumen tapes to steel pipelines, concrete surfaces/culverts and fittings.

### **Features**

- Fills surface irregularities for intimate contact of bitumen tape compound
- Promotes high adhesion
- Resists degradation in aggressive industrial and climatic conditions
- Fast drying
- Highly resistant to mineral acids, alkali and salts
- Can be brush or spray applied

### **Application**

Prepare steel to St2 (power brushed) / AS1627 P.2 (minimum), if required. Edges on existing adjacent coatings should be chamfered to remove step down. Abrade approximately 100 mm band of pre-existing factory coatings and degrease using solvent (toluene) either side of the joint.

Note: concrete surfaces must be well cured and dry with all loose material removed from surface.

Thoroughly stir the primer in its container to ensure uniformity prior to use. Brush, sponge or spray apply an even coating at a rate of 9-11 m<sup>2</sup>/L.



# Denso Primer D

## PROPERTY SPECIFICATIONS

| <b>PROPERTIES</b>       | <b>VALUE</b>           |
|-------------------------|------------------------|
| Specific Gravity        | 0.92                   |
| Solids Content          | 60%                    |
| Viscosity (AG:PT/T111)  | 200 ± 50 cP            |
| Drying Time (Tack Dry)  | 10 - 15 min @ 20°C     |
| Flash Point             | > 24°C (closed cup)    |
| Application Temperature | 0°C to 55°C            |
| Service Temperature     | -20°C to 65°C          |
| Coverage Capacity       | 9-11 m <sup>2</sup> /L |

### PACKAGING:

1 L (6/carton)

4 L (2/carton)

20 L Pail



**DENSO (AUSTRALIA) PTY LTD**

77 - 95 National Boulevard

Campbellfield, VIC 3061

Tel: +61 3 9356 7600

Fax: +61 3 9356 7699

[www.densoaustralia.com.au](http://www.densoaustralia.com.au)

**A Member of the Winn & Coales International**

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.