

DENSO GLASS OUTERWRAP UV

UV Protective Fiberglass Outerwrap

Description

Denso Glass Outerwrap UV is a fiberglass cloth impregnated with a water activated aliphatic polyurethane resin that is used as a protective outer wrap over Denso Petrolatum Tape.

Uses

A protective coating which offers exceptional mechanical and impact strength for underwater, underground and above ground pipe and piles. The aliphatic polyurethane provides UV stability.

Features

- UV resistant
- Resists cold and hot temperatures
- Easy to apply, no mixing or messy clean up
- Resistant to water, acid, salts, or soil organics
- Can be applied underwater or to wet surfaces
- Minimal surface preparation required
- Quick, long-term protective coating, ready for immediate service
- Contains no solvents
- Can be top coated for aesthetics

Application

Prepare surfaces by removing all loose scale, rust or other foreign matter in accordance to SSPC SP2 "Hand Tool Cleaning" or SP3 "Power Tool Cleaning". High pressure water wash of 20 to 48 MPa is also suitable. Spirally wrap a layer of Denso Tape at a 55% overlap. While wrapping, press air pockets out and smooth all lap seams.

Using rubber gloves, remove the Denso Glass Outerwrap from the hermetically sealed foil pouch and soak in temperate water (salt or fresh) for 20 to 30 seconds. Remove and begin wrapping tightly, overlapping at a recommended 55%.

Irregular surfaces such as valves, flanges, etc. may require the use of Denso Mastic, Densyl Mastic or Denso Profiling Mastic. Refer to the individual product data sheets for information on specific products and application.



Denso Glass Outerwrap UV

Property Specifications

PROPERTIES	VALUE
Colour	Grey
Flexural Strength (ASTM D709-71)	113,200 kg/mm ²
Tensile Strength (ASTM D638)	175,071 kg/mm ²
Compression Strength (ASTM D695-77)	187,024 kg/mm ²
Dielectric Strength	16 kV
Maximum Service Temperature	177°C
Setting Time	
21°C	2.5 h
32°C	1 h
Product Sizes	75 mm x 2.7 m
	100 mm x 9 m
	200 mm x 12 m

SHELF-LIFE: 6 months

STORAGE: In original cartons and a cool, dry place away from direct sunlight.



DENSO (AUSTRALIA) PTY LTD

77 - 95 National Boulevard
Campbellfield, VIC 3061

Tel: +61 3 9356 7600

Fax: +61 3 9356 7699

www.densoaustralia.com.au

A Member of the Winn & Coales International

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.