

STEELCOAT 200™ SYSTEM



A petrolatum tape system for the protection of above ground pipelines operating at elevated service temperatures

The Steelcoat 200™ System comprises a polymer backed petrolatum tape (Denso Hotline™ Tape) and a high temperature mastic for sealing fittings in awkward shapes (Densoseal 16A™). No primer is required.

The system is designed to protect copper, iron or steel pipes that run at high temperatures, up to 110°C maximum (83°C if the pipe is buried), located above ground in ducts or set in concrete.

FEATURES

- No primer required
- Cold applied
- For service temperatures up to 110°C maximum
- Surface tolerant
- Can be applied by hand or wrapping machine

COMPONENTS

Denso Hotline™ Tape

Applied with a 55% overlap by either hand or machine application.

Densoseal 16A™

Denso Glass OuterWrap

Denso Sirex Tape

SURFACE PREPARATION

Minimal surface preparation required.

Surfaces must be clean and dry. Remove all loose rust, scale and flaking coatings by hand wire brush.



Ver 2203.01

DENSO (AUSTRALIA) PTY LTD

TEL: +61 (03) 9356 7600

FAX: +61 (03) 9356 7699

EMAIL: denso@densoaustralia.com.au

WEB: www.densoaustralia.com.au

77-95 National Boulevard

Campbellfield,

Victoria 3061

AUSTRALIA



ISO 9001:2015

