

# DENSO SEASHIELD™ PRIMER

## Wet/Underwater Petrolatum Tape Primer

### Description

Denso SeaShield™ Primer is a soft petrolatum primer containing water displacing corrosion inhibiting and flow control additives. The primer can be applied by gloved hand or stiff bristle brush.

### Uses

Denso SeaShield™ Primer serves as a corrosion inhibitor and aids in the application of petrolatum tapes. It is very effective underwater or on very wet metal surfaces such as pilings, risers, and H-piles.

### Features

- Applied to marginally prepared surfaces (SSPC SP 2-3)
- Applied to very wet or underwater surfaces
- Contains no V.O.C.'s
- Can be applied by inexperienced personnel
- No shut downs necessary
- No cure time
- Meets AWWA C-217

### Application

Prepare surfaces by removing all loose scale, rust or other foreign matter in accordance to SSPC SP2 "Hand Tool Cleaning" or SP3 "Power Tool Cleaning". High pressure water wash of 3,000 - 7,000 psi (20.68 - 48.26 MPa) is also suitable. Apply a thin uniform coat of Denso SeaShield™ Primer to entire surface with gloved hand, brush or rag.



# Denso SeaShield™ Primer

## PROPERTY SPECIFICATIONS

PROPERTIES	VALUE
Solids Content	100%
Specific Gravity	1.08
Specific Volume	925 cc/kg
Flash Point	>180°C
Maximum Service Temperature	70°C
Coverage	1 to 2 m <sup>2</sup> /kg
Packaging	4 ea 2.5 kg tubs

### COVERAGE:

484 ft<sup>2</sup> per case for dry & wet surfaces  
(22 m<sup>2</sup> per case for dry & wet surfaces)

220 ft<sup>2</sup> per case for underwater applications  
(11 m<sup>2</sup> per case for underwater applications)

### PACKAGING:

4 each 5.5 lb tubs per case  
(4 each 2.5 kg tubs per case)

Also available in 33 lb (15 kg) drums



**DENSO (AUSTRALIA) PTY LTD**

77-95 National Boulevard

Campbellfield, VIC 3061

Tel: +61 3 9356 7600

Fax: +61 3 9356 7699

[www.densoaustralia.com.au](http://www.densoaustralia.com.au)

***A Member of Winn & Coales International***

The information given on this sheet is intended as a general guide only and should not be used for specification purposes. We believe the information to be accurate and reliable but do not guarantee it. We assume no responsibility for the use of this information. Users must, by their own tests, determine the suitability of the products and information supplied by us for their own particular purposes. No patent liability can be assumed.