

# DENSOSEAL 16A™

A FIRM, FIBROUS  
MASTIC FOR THE  
SEALING OF SERVICE  
ENTRIES AND DUCTS.



Densoseal 16A™ is a self supporting non-setting mastic which has been developed for sealing cable ducts and conduits against gas or water. It also has British Telecom type approval.

- Adheres to glazed earthenware, steel and unplasticised materials such as lead, polythene or PVC.
- Unaffected by natural gas and water.
- Accommodates movement.
- Adheres to wet surfaces.
- Withstands at least 20kPa (2 metre head) water pressure for a minimum of 30 minutes.

## COMPOSITION

A firm fibrous mastic based on polybutene, mineral fillers, organic fibres and water displacing materials. Preformed strip.

## FIELD OF APPLICATION

Gas and water can accumulate in underground ducts such as those carrying telephone or electricity supply cables. Where ducts terminate inside buildings, manholes or chambers they must be sealed against gas and water. Densoseal 16A is especially suitable for those applications where ducts are wet or liable to fill with water.

## METHOD OF APPLICATION

Densoseal 16A is packed into the ends of the duct by hand and moulded firmly around cables and against the duct ensuring there are no gaps or fissures. The mastic should be packed to a depth at least equal to the diameter of the duct. Surfaces should be free from loose rust, scale, dirt or previous sealants.



VER 2508.20



ISO 9001:2015

## DENSO (AUSTRALIA) PTY LTD

TEL: +61 (03) 9356 7600  
FAX: +61 (03) 9356 7699  
EMAIL: [info@densoaustralia.com.au](mailto:info@densoaustralia.com.au)  
WEB: [www.densoaustralia.com.au](http://www.densoaustralia.com.au)

77-95 National Boulevard  
Campbellfield,  
Victoria 3061  
AUSTRALIA

