

# STEELCOAT™ COLUMN BASE PROTECTION SYSTEM



A surface tolerant system providing a long-term protective coating for column bases in corrosive environments

The Steelcoat™ Column Base Protection System comprises of Denso Hi-Tack™ Primer to coat the cleaned substrate and Denso Profiling Mastic™ is used to fill any voids and to build up any angles required to create a smooth profile. A layer of Denso Hi-Tack™ Tape is then applied over the area followed by a layer of Denso D10™ Scrim. A coat of Denso Basecoat™ is applied to complete the protective system. An optional acrylic topcoat is available.

## FEATURES

- Cold applied
- Surface tolerant
- Hand applied
- Flexible and mouldable for awkward shapes and angles
- Long-term protection

## COMPONENTS

- Denso Hi-Tack™ Primer
- Denso Profiling Mastic™
- Denso Hi-Tack™ Tape
- Denso D10™ Scrim
- Denso Basecoat™
- Options:
  - Denso Acrylic Topcoat™

## SURFACE PREPARATION

Minimal surface preparation required. Surfaces must be clean and dry. Remove all loose rust, scale and flaking coatings by hand wire brush.



VER 1603.21



ISO 9001:2015

## DENSO (AUSTRALIA) PTY LTD

TEL: +61 (03) 9356 7600  
FAX: +61 (03) 9356 7699  
EMAIL: [info@densoaustralia.com.au](mailto:info@densoaustralia.com.au)  
WEB: [www.densoaustralia.com.au](http://www.densoaustralia.com.au)

77-95 National Boulevard  
Campbellfield,  
Victoria 3061  
AUSTRALIA



A MEMBER OF WINN & COALES INTERNATIONAL